



Available Colors: Black/Yellow,
Black, Gray



Airug® is a low cost solution for workstations where workers are standing for long periods of time and basic anti-fatigue is needed. The PVC closed cell foam relieves leg and back discomfort while providing a barrier to cold floors.

Test	Test Description	*Results
ASTM C1028-96	Static Coefficient of Friction	Dry: .80
-	Compression Deflection	@ 20 lbs./in ² : 0.211 in. @ 40 lbs./in ² : 0.269 in.
ASTM D2240-02	Durometer (Shore A)	15
CPSC FF 1-70 (ASTM D-2859)	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass
ASTM D1004-94a-03	Tear Strength	7.0 lbs.
ASTM D412	Elongation/Tensile	81.5 lbs./in ²
ASTM D3884-01	Abrasion Resistance (Measured in % weight loss)	@2500 cycles: (33.62%)

*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.
(NOTE - Test results based on 3/8" thickness)

12/2014



Anti-Fatigue



Custom Sizes

- PVC closed cell foam
- Thickness: 3/8", 5/8"
- Beveled edges on all four sides
- Stock Sizes: 27" x 3', 27" x 5', 2' x 3', 3' x 5', 3' x 12'
- Roll Sizes: 2' x 60', 3' x 60', 4' x 60', 6' x 60'
- Custom Sizes: In 2', 3', and 4' widths (up to 60')