

The dexterity of a heavy duty unlined style wet/oily grip performance of ANSELL GRIP™ technology

- 58-435 high duty level combines the market leading performance of ANSELL GRIP technology with the flexibility and dexterity of an unlined nitrile shell.
- This unique, patented design features a premium grade nitrile compound coating (for versatile chemical protection and long-lasting snag, puncture and abrasion resistance) along with comfortable cotton-flocked liner.
- The glove is ideal for intermittent exposure to lubricants and cleaning agents in industrial settings.

Industries

- Automotive
- Automotive Aftermarket
- Machinery and Equipment
- Metal fabrication
- Chemical

Applications

- Metalworking & assembly operations
- Body painting including surface inspection
- Applying sealers, touching up
- Painting or cleaning tools or robots
- Changing tools and dies
- Handling application & cleaning tools
- Warehousing of raw materials
- Loading and unloading of process equipment
- Transferring liquids and solids between vessels and tanks and process equipment
- Opening furnaces draining pumps valves or lines and crackers BTX process



Key Features

- ANSELL GRIP technology ensures optimal control and confidence when handling oily or wet objects and requires less force to control slippery objects, reducing hand and arm fatigue
- Creates safe and secure glove contact with tools or part surfaces by wicking liquids into glove coating micro-channels
- The heavy-duty 58-435 has a 16-mil shell effective against hydrocarbon derivatives, alcohol bases, many solvents and esters.
- The nitrile coating offers superior snag, puncture and abrasion protection for long-term wear. A foldable gutter cuff helps prevent dripping onto the forearm, while an extra-long cuff (58-435) extends protection to the upper forearm
- Longer version than the 58-430 for further protection
- Compliant with FDA food handling requirements

Vulcanization Chemical Accelerators

- Zinc Diethyldithiocarbamate

Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.

Performance Standards



Specifications

BRAND STYLE	DESCRIPTION	SIZE	LENGTH	COLO R	PACKAGE
AlphaTec® 58-435	Cotton Flocking, Nitrile, Ansell Grip™	7, 8, 9, 10, 11	380 mm/ 15 inches	Grey	• 12 pairs/polybag; 6 polybags/carton; 72 pairs/carton

Europe, Middle East & Africa Region
 Ansell Healthcare Europe NV
 Riverside Business Park
 Blvd International, 55
 1070 Brussels, Belgium
 T: +32 (0) 2 528 74 00
 F: +32 (0) 2 528 74 01

North America Region
 Ansell Healthcare Products LLC
 111 Wood Avenue South,
 Suite 210
 Iselin, NJ 08830, USA
 T: +1 800 800 0444
 F: +1 800 800 0445

Latin America & Caribbean Region
 Ansell Commercial Mexico S.A. de C.V.
 Blvd. Bernardo Quintana No. 7001-C,
 Q7001 Torre II,
 Suites 1304, 1305 y 1306.
 Col. Centro Sur, c.p. 76079
 Queretaro, Qro. Mexico
 T: +52 442 248 1544 / 248 3133

Canada
 Ansell Canada Inc.
 105, rue Lauder
 Cowansville (Québec)
 J2K 2K8, Canada
 T: 1800 363-8340
 F: 1888 267-3551

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2019 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

Technologies

