



**ARMOR GUYS**  
• PROTECTED •

**TAEKI5**

## 01-002 SPECIFICATION SHEET



### SPECIFICATIONS

<b>LINER MATERIALS</b>	Yellow 100% Taeki5® Liner
<b>COATING MATERIALS</b>	Blue Crinkle Latex
<b>WRIST DESIGN</b>	Continuous Knit
<b>SIZES</b>	XS- XXL
<b>PACKAGING</b>	1 pair per dozen, 12 pairs per dozen, 120 Pairs per case
<b>CASE</b>	XS S M L XL XXL
<b>WEIGHT</b>	27.75/lbs 29.07/lbs 32.16/lbs 33.48/lbs 35.24/lbs 35.24/lbs
<b>CUFF COLOR</b>	Purple Red Yellow Brown Black Blue
<b>ORIGIN</b>	PRC

### PERFORMANCE LEVEL

EN388: 4542		EN Level 5 Cut Resistance					
ABRASION	0	1	2	3	4	5	
CUT	0	1	2	3	4	5	
TEAR	0	1	2	3	4	5	
PUNCTURE	0	1	2	3	4	5	

### TECHNOLOGIES:



### ATTRIBUTES:

#### LINER

10g, Yellow  
100% Taeki5® Liner

#### COATING

Blue Crinkle Latex  
Palm Coating

### FEATURES:

ANSI Cut Level A3  
EN388 Cut Level 5  
Excellent Cut Resistance  
Excellent Heat Resistance  
Excellent Abrasion Resistance  
UV Light Resistance  
Lint Free  
Moisture Wicking

### RANGE:

Taeki5®

### APPLICATIONS:

Construction  
Glass Handling  
Mining  
Steel Manufacturing  
Wood Handling

Armor Guys reference number : 01-002

Performance	TAEKI5®	HDPE* UHMWPE**	META-ARAMID PARA- ARAMID
Abrasion resistance	++	++	-
Cut resistance	++	+	-
Heat contact resistance	+	x	+
Washing	++	+	-
UV resistance	++	++	x
Lint free	++	++	x
Any Color available	++	-	-
Comfort	++	++	+
Variety of coating available including Nitrile, PVC and Latex	++	-	+
Quality/price ratio	++	-	+
<b>Total Performance</b>	+29	+19	+12

\* HDPE = High Density Polyethylene

\*\* UHMWPE = Ultra High Molecular Weight Polyethylene

Testing method based on both CE and ANSI standard

3 ++ HIGH

1 - LOW

2 + MEDIUM

0 x NO

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)