



**ARMOR GUYS**  
• PROTECTED •

**ULTIMATE**

**TAEKI5**  
Advanced Composite Fiber

**01-019      SPECIFICATION SHEET**



## DIMENSIONS

Length: 18 inch

## SPECIFICATIONS

<b>LINER MATERIALS</b>	Hi-Vis Yellow Taeki5® Fiber
<b>WRIST DESIGN</b>	Continuous Knit
<b>SIZES</b>	One Size
<b>PACKAGING</b>	Single Sleeves Individually Packaged, 120 Sleeves In Each Case
<b>LENGTH</b>	18 inch / 45cm
<b>CASE WEIGHT</b>	20.70/lbs
<b>ORIGIN</b>	PRC

## PERFORMANCE LEVEL

EN388: 454X	En Level 5 Cut Resistance					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5

## CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)



## FEATURES:

### LINER

18" Hi Vis Yellow 100% Taeki5® Sleeve  
Without thumb hole

## BENEFITS:

ANSI Cut Level A4  
EN388 Cut Level 5  
Excellent Cut Resistance  
Excellent Heat Resistance  
Excellent Abrasion Resistance  
UV Light Resistance  
Lint Free  
Moisture Wicking

## RANGE:

Ultimate

## APPLICATIONS:

Appliance Manufacturing  
Automotive Assembly  
HVAC/Sheet Metal  
Metal Fabrication  
Recycling

**Armor Guys reference number : 01-019**

Performance	TAEKI5®	HDPE* UHMWPE**	META-ARAMID PARA-ARAMID
Abrasion resistance	++	++	-
Cut resistance	++	+	-
Heat contact resistance	+	×	+
Washing	++	+	-
UV resistance	++	++	×
Lint free	++	++	×
Any Color available	++	-	-
Comfort	++	++	+
Variety of coating available including Nitrile, PVC and Latex	++	-	+
Quality/price ratio	++	-	+
<b>Total Performance</b>	+29	+19	+12

\* HDPE = High Density Polyethylene

\*\* UHMWPE = Ultra High Molecular Weight Polyethylene

Testing method based on both CE and ANSI standard

3 | ++ | HIGH

1 | - | LOW

2 | + | MEDIUM

0 | x | NO