



ARMOR GUYS
• PROTECTED •

ULTIMATE

TAEKI5
Advanced Composite Fiber

01-020 SPECIFICATION SHEET

FEATURES:

LINER

10g, Yellow
100% **Taeki5®** Liner

COATING

Gray Sewn on Leather
Palm Liner

BENEFITS:

ANSI Cut Level A4
EN388 Cut Level 5
Excellent Cut Resistance
Excellent Heat Resistance
Excellent Abrasion Resistance
UV Light Resistance
Lint Free
Moisture Wicking

RANGE:

Ultimate

APPLICATIONS:


Construction
Heavy Manufacturing
HVAC/Sheet Metal
Metal Fabrication
Steel Handling
Recycling

Armor Guys reference number : 01-020



DIMENSIONS (Inches)

	L	XL	XXL
A	9.8	10.2	10.6
B	4.9	5.1	5.5
H	Brown	Black	Light Blue



SPECIFICATIONS

LINER MATERIALS	Yellow 100% Taeki5® Liner		
COATING MATERIALS	Gray Sewn on Leather		
WRIST DESIGN	Continuous Knit		
SIZES	L - XXL		
PACKAGING	1 pair in an individual polybag, 12 pairs per dozen, 60 pairs per case		
CASE WEIGHT	L	XL	XXL
	19.8/lbs	22/lbs	24.3/lbs
ORIGIN	PRC		

PERFORMANCE LEVEL

EN388: 4542	EN Level 5 Cut Resistance					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

Performance		TAEKI5®	HDPE* UHMWPE**	META-ARAMID PARA- ARAMID
	Abrasion resistance	++	++	-
	Cut resistance	++	+	-
	Heat contact resistance	+	×	+
	Washing	++	+	-
	UV resistance	++	++	×
	Lint free	++	++	×
	Any Color available	++	-	-
	Comfort	++	++	+
	Variety of coating available including Nitrile, PVC and Latex	++	-	+
	Quality/price ratio	++	-	+
Total Performance		+29	+19	+12

* HDPE = High Density Polyethylene

** UHMWPE = Ultra High Molecular Weight Polyethylene

Testing method based on both CE and ANSI standard

3 ++ HIGH 1 - LOW
2 + MEDIUM 0 x NO