



## DIMENSIONS

Length: 22 inch

## SPECIFICATIONS

LINER MATERIALS	Yellow 100% <b>Taeki5®</b> Fiber
COATING MATERIALS	Yellow
SIZES	One Size
PACKAGING	Single Sleeves Individually Packaged, 120 Sleeves In Each Case

## PERFORMANCE LEVEL

EN388: 454X	En Level 5 Cut Resistance					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5

## CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

## FEATURES:

### LINER

22" Yellow 100% **Taeki5®** Sleeve with clips

## BENEFITS:

ANSI Cut Level A4  
EN388 Cut Level 5  
"All in one" : Fit, Feel, Flexibility, Breathability, Durability  
Improved Cut  
Improved Abrasion Resistance  
Improved Heat  
UV Light Resistance  
Lint Free  
Cool Feel To Hand

## RANGE:

**Ultimate**

## APPLICATIONS:

Aerospace  
Appliance Manufacturing  
Automotive  
General Carpentry  
Glass  
HVAC/Sheet Metal Users/Window Glaziers  
Lumber/Wood/Paper  
Metal Fabrication  
Metalworking  
Plastics

**Armor Guys reference number : 01-021**

Performance	<b>TAEKI 5®</b>	HDPE* UHMWPE**	META-ARAMID PARA-ARAMID
Abrasion resistance	++	++	-
Cut resistance	++	+	-
Heat contact resistance	+	×	+
Washing	++	+	-
UV resistance	++	++	×
Lint free	++	++	×
Any Color available	++	-	-
Comfort	++	++	+
Variety of coating available including Nitrile, PVC and Latex	++	-	+
Quality/price ratio	++	-	+
<b>Total Performance</b>	+29	+19	+12

\* HDPE = High Density Polyethylene

\*\* UHMWPE = Ultra High Molecular Weight Polyethylene

Testing method based on both CE and ANSI standard

++ HIGH - LOW

+ MEDIUM x NO