



ARMOR GUYS
• PROTECTED •

EXCEL

BASETEK
Innovative Fiber Technology

02-008 SPECIFICATION SHEET

FEATURES

LINER

13g, Gray **Basetek** Liner

COATING

Gray Polyurethane Palm Coating

BENEFITS:

ANSI Cut Level A2
EN388 Cut level 3
Improved Grip and Abrasion Resistance
Repels Liquids From Palm of Hand

CATEGORY:

Excel

APPLICATIONS:

Aerospace
Appliance Manufacturing
Automotive Assembly
HVAC/Sheet Metal
Metal Fabrication
Parts Assembly
Pulling Electrical Wires

Armor Guys reference number : 02-008

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)



CE




DIMENSIONS (Inches)

	XS	S	M	L	XL	XXL
A	8.7	9.0	9.4	9.8	10.2	10.6
B	3.4	3.6	3.7	3.8	3.9	4.2

SPECIFICATIONS

LINER MATERIALS	Gray Basetek Liner
COATING MATERIALS	Gray Polyurethane
WRIST DESIGN	Continuous Knit



PACKAGING						
CASE SIZE	XS	S	M	L	XL	XXL
PER CARTON	144	144	144	144	144	144
CASE WEIGHT	17.08/lbs	17.85/lbs	18.84/lbs	20.06/lbs	20.83/lbs	22.48/lbs
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
ORIGIN	PRC					

PERFORMANCE LEVEL

EN388: 4342	EN Level 3 Cut Resistance					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5