


Professional Grade Duct Tape (Metallic)



Backing
Adhesive



Backing: Metallized PE Coated Cloth
Adhesive: Rubber
Liner: N/A
Colors: Metallic

Specifications: Tested in accordance with UL 723

Standard Sizes: 48mm x 55m, 72mm x 55m

Applications

- Duct sealing and HVAC contractor uses
- Maintenance applications in manufacturing environments
- General repair
- Bundling, patching, and mending

Features

- Metallized PE-Coated Cloth Backing
- Natural Rubber Based Adhesive
- Low VOC Content

Benefits

- Excellent balance of tensile strength and tearability
- Aggressive adhesion to rough surfaces
- Superior holding power for hanging applications
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

| | Standard UOM | Metric UOM | Test Method |
|------------------------------|--------------|------------|-------------|
| Total Thickness | 11.0 mils | 0.279 mm | ASTM D-1000 |
| Adhesion to Steel | 70 oz/in | 7.66 N/cm | PSTC-101 |
| Adhesion to Backing | 48 oz/in | 5.25 N/cm | PSTC-101 |
| Tensile Strength | 23 lb/in | 40.28 N/cm | ASTM D-1000 |
| Elongation | 24% | | ASTM D-1000 |
| Operating Temperature | 40 to 200 °F | 4 to 93 °C | |
| Smoke Developed | 5 | | |
| Flame Spread | 10 | | |
| VOC Content | <1 g/L | | |

Recommended Storage Conditions: 32-90 °F at 50% RH ± 2%

Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.