

DRYWALL TAPE



DESCRIPTION

This tape is made of a 100% fiberglass mesh coated with a water based acrylic adhesive.

MAIN FEATURES

- Faster and easier to use -- stays in place without pre-plastering!
- Strong fiberglass mesh imbeds in plaster or drywall joint compounds to resist cracks.
- Easy to apply and reposition if needed.
- Low adhesion, yet stays firmly in place while being plastered.

APPLICATIONS

For repairing and reinforcing cracks in drywall, plaster and stucco.

STAYS IN PLACE

FASTER AND EASIER TO USE

TECHNICAL DATA

Colour	White
Backing	White Fiberglass Yarn / Leno Weave
Adhesive	Latex based Acrylic
Thickness	9.8 mil
Adhesion to steel	3.6 oz/in
Tensile strength – Wrap direction	40 lb/in
Tensile strength – Fill direction	34 lb/in
Elongation	4%

Please note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

