



NATIONAL  
SAFETY APPAREL®

# DRIFIRE FR Utility Shirt



## Specs

Product Code DF2-324LS-\_\_

Stock Sizes SM-3X, RG | MD-3X, TL

Stock Colors

Fabric / Material 7 oz. DRIFIRE® Twill

## Compliance

---

Arc Rating	12 cal/cm <sup>2</sup>
CAT Level	CAT 2
Standards	<ul style="list-style-type: none"><li>• NFPA 70E</li><li>• ASTM F1506</li><li>• CSA Z462</li><li>• OSHA 1910.269</li></ul>

## Features

---

Features	<ul style="list-style-type: none"><li>• Lightweight, breathable fabric</li><li>• Moisture-wicking technology to keep you dryer</li><li>• FR fabric will not melt, drip, or ignite</li><li>• Inherently flame resistant, FR protection will not wash/wear out</li><li>• Features two chest pockets with button closure</li><li>• Quickly identify compliance with exterior labeling</li><li>• Odor control technology</li><li>• Dries 2-3 times faster than typical FR utility shirts</li><li>• Longer tail stays tucked in</li><li>• Dual certified to protect against flash fire and arc flash hazards</li><li>• Made in the USA</li></ul>
----------	---

## Product Care

---

Product Care	<ul style="list-style-type: none"><li>• READ THE GARMENT LABEL AND LAUNDER PER INSTRUCTIONS ON GARMENT LABEL.</li><li>• DO NOT use chlorine bleach or detergents containing bleach. DO NOT use fabric softeners. DO NOT iron.</li><li>• Wash/Laundering Instructions: Machine wash warm. Tumble dry low.</li><li>• Wash according to the instructions above to remove any contaminants in order to maintain fabric performance when garment becomes soiled with dirt, greases, oils, etc.</li><li>• If contaminants cannot be removed after laundering, it is best to discontinue use of garment.</li></ul>
--------------	---

## Sizing Chart

---

**NSA, VIZABLE® & DRIFIRE® Work Shirts (SHR-RG)**

\*Does not Include DRIFIRE HI-VIS Work Shirts

Size	Chest	Center Back	Sleeve Length
<b>SM</b>	32" - 35"	31.375"	34.5"
<b>MD</b>	36" - 39"	31.875"	35.5"
<b>LG</b>	40" - 43"	32.375"	36.5"
<b>XL</b>	44" - 47"	32.875"	37.5"
<b>2X</b>	48" - 51"	33.375"	38.5"
<b>3X</b>	52" - 55"	33.875"	39.5"
<b>4X</b>	56" - 59"	34.125"	40.5"
<b>5X</b>	60" - 63"	34.625"	42.5"