



|                    |   |                           |
|--------------------|---|---------------------------|
| Materials/Finishes | Plain Carbon Steel (24LB)                                 | Electro-Galvanized (24LG) |
| Variants:          | N/A   |                           |
| Service:           | Designed for use with large-lip steel Purlin beams        |                           |
| Approvals:         | N/A   |                           |
| Ordering:          | Specify figure number and finish                          |                           |
| Notes:             | See MSS SP-69 for proper set screw torque recommendations |                           |

| SIZE<br>A | SET<br>SCREW | B | C | D     | E     | WGT EACH<br>(lbs) | MAX REC<br>LOAD (lbs) |
|-----------|--------------|---|---|-------|-------|-------------------|-----------------------|
| 3/8-16    | 3/8-16 x 3   | 1 | 1 | 1-7/8 | 1-5/8 | 0.92              | 400                   |

| PROJECT INFORMATION |                   |              | APPROVAL STAMP |  |
|---------------------|-------------------|--------------|----------------|--|
| Project:            |                   |              | Notes:         |  |
| Address:            |                   |              |                |  |
| Contractor:         |                   |              |                |  |
| Engineer:           |                   |              |                |  |
| Date:               |                   |              |                |  |
| Approved            | Approved as Noted | Not Approved |                |  |