

ENERPAC
POWERFUL SOLUTIONS. GLOBAL FORCE.

For use with Cylinder Capacity	Saddles			Base Plate	Mounting Block	Clevis Eyes	
	Flat	Grooved ¹⁾	Tilt			Base ⁴⁾	Plunger
ton (kN)							
5 (45)	A-53F ²⁾	A-53G ²⁾	–	–	RB-5 ²⁾ , AW-51 ²⁾ , AW-53 ²⁾	REB-5 ²⁾	REP-5 ²⁾
10 (101)	A-12 ⁵⁾ , A-102F ³⁾	A-102G ³⁾	CAT-10 ³⁾	JB1-10	RB-10, AW-102	REB-10	REP-10 ³⁾
15 (142)	–	A-152G	CAT-10	–	RB-15	REB-15	REP-10
25 (232)	A-29 ⁵⁾	A-252G	CAT-50	JB1-25	RB-25	REB-25	REP-25
30 (295)	A-29 ⁵⁾	A-252G	CAT-50	–	RB-25	–	REP-25
50 (498)	–	–	CAT-100	JB1-50	–	–	–
75 (718)	–	–	CAT-100	–	–	–	–
95 (933)	–	–	CAT-100	–	–	–	–

¹⁾ Standard on 5-30 ton RC-cylinders ²⁾ Except RC-50 ³⁾ Except RC-101 ⁴⁾ Mounting screws are included. ⁵⁾ Used with Bender Sets.

Model Number	Saddle Dimensions (mm)			A-53F, A-102F	Model Number	Tilt Saddle Dimensions (mm)			
	A	B	C			A	B	C	
	Flat					Tilt			
A-53F	25	6	17	A-12, A-29	CAT-10	35	15	22	
A-102F	35	6	22		CAT-50	50	23	35	
A-12	51	48	1"-8 UNC						
A-29	51	48	1½"-16 UNC						
Grooved			Tilt						
A-53G	25	6	17		CAT-100	71	24	—	
A-102G	35	6	22						
A-152G	38	9	22						
A-252G	50	9	35						

Model Number	Base Plate Dimensions Dimensions (mm)				
	A	B	C	D	E
JB1-10	228	228	135	58	20
JB1-25	279	279	140	86	26
JB1-50	304	15	95	131	31




JB1-10. 25




JB1-50

Model Number	Mounting Block Dimensions (mm)							
	A	B	C	D	E	F	G	H
RB-5	1½"-16UN	88	76	—	25	—	—	—
AW-51	1½"-16UN	70	59	10	24	54	¼"-16 UN	41
AW-53	1½"-16UN	72	7	7	19	57	¼"-20 UN	10
RB-10	2¼"-14UN	114	88	—	25	—	—	—
AW-102	2¼"-14UN	100	82	16	30	76	7/16"-20 UN	58
RB-15	2¾"-16UN	101	114	—	38	—	—	—
RB-25	3¾"-12UN	127	165	—	50	—	—	—




RB-5, -10
RB-15, -25



AW-51



AW-53



AW-102 (I=4,8)

Type	Model Number	Cleviss Eye Dimensions (mm)						Pin-to-Pin * (mm)
		A	B	C	D	E	F	
Base ⁴⁾	REB-5	44	47	14	16	16	25	60,2
	REB-10	63	66	25	22	25	35	78,0
	REB-15	76	66	25	22	25	35	78,0
	REB-25	95	79	38	31	31	41	87,6
Plunger	REP-5	28	45	14	16	16	19	-
	REP-10	42	61	25	22	25	28	-
	REP-25	57	71	38	31	31	35	-

REB

REP

4) Mounting screws are included.

* Pin to Pin – REB and REP Clevises fitted. Add cylinder collapsed height.