

## GFCI In-Line Cord Sets with Molded Locking Connectors



26020 097-6

### GFCI In-Line Cord Sets with Molded Locking Connectors

Excellent for industrial plant maintenance, equipment service and construction site applications. Provides compliance with National Electric Code (NEC 2008) Article 590.6 for "Temporary Installations." Applications include:

- ▶ High Pressure Sprayer Washers
- ▶ Drain Snakes
- ▶ Construction Sites
- ▶ Construction Site Power Tools
- ▶ Pumps
- ▶ Industrial Appliances

Rainproof rated, UL listed for outdoor use. Standard Lengths: 2', 6'. Custom cable gauges, lengths and terminations available by special order. To prevent unmonitored equipment startup, manual reset is required after GFCI trip and power outage.

#### FEATURES

##### 26020 097-6 (2') ☺

- ▶ Volts /Amps: 120V/15A
- ▶ Cord Gauge: 14/3 AWG
- ▶ NEMA L5 - 15 P & R
- ▶ Trip Level: 4-6 mA

##### 25080 136-6 (2') ☺

##### 25080 137-3 (6') ☺

- ▶ Volts /Amps: 120V/20A
- ▶ Cord Gauge: 12/3 AWG
- ▶ NEMA L5 - 20 P & R
- ▶ Trip Level: 4-6 mA



#### TECHNICAL DATA

Grounded Neutral	4 Ohms typical
Trip response time for ground fault and grounded neutral trip	less than 25mS
Voltage surge withstand	3kv ringwave test and 4kv/2kA surge immunity test
Radio frequency noise susceptibility	operates within normal limits with 0.5 volts injected on power line 150kHz-230mHz
Frequency	50 / 60 Hz
Endurance	3,000 operations minimum
Overload Current	six times rated current
Operating temperature range	-35°C to 66°C
Effect of 10 Amp turn DC Shock on ground fault trip	5% maximum trip level variation
Insulation voltage	1500 VRMS - 1 Min.
Power On indication	lighted indicator

