

TECHNICAL DATA**KKP-06****KRUD KUTTER® PRO
DRAIN OPENER****DESCRIPTION AND USES**

Krud Kutter® PRO Drain Opener starts working immediately to clear blocked drains. This professional strength gel formula powers through standing water to remove all types of stubborn clogs, hair, soap scum and grease.

PRODUCT

SKU	DESCRIPTION
352236	32 oz. Bottle

PRODUCT APPLICATION**READ ALL DIRECTIONS CAREFULLY BEFORE
STARTING PROJECT**

Open carefully. Do not squeeze bottle. Avoid splashing. Clean up spills at once. Keep hands, face and children away from drains while using product. **DO NOT USE IN TOILETS OR WITH PLUNGER.**

DIRECTIONS

1. Shake well before use (make sure the cap is securely closed).
2. Pour 16 oz. (1/2 bottle) slowly into drain opening.
3. Wait at least 10 minutes. For tough problems, wait longer.
4. Flush with hot tap water. Repeat steps 2, 3, & 4 if necessary.

PRODUCT APPLICATION (cont.)**DIRECTIONS (cont.)**

Garbage Disposals: Follow same directions. Rinse thoroughly after use. If clog has not cleared, do not turn on disposal as product may splash. Contact a plumber.

PREVENTION

Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing should not be allowed out of the workplace.

IMPORTANT: Do not reuse empty container. Rinse container and replace cap before discarding.

Do not use Drain Cleaner with ammonia, toilet bowl cleaners or other drain openers as splashing or the release of hazardous gases may occur. If gases are released, leave area immediately, ventilate area.

PHYSICAL PROPERTIES

	DRAIN OPENER
Composition	Sodium Hypochlorite, Sodium Hydroxide, Biodegradable Surfactant, Soap, and Sodium Silicate
Color	Slight Yellow
Clarity	Hazy
pH	12.5-13.5
VOC	0% By Weight
Dwell Times	15 minutes (where applicable)
Practical Coverage	Varies with application type
Shelf Life	1 year
Flash Point	>200°F (>93°C)
Safety Information	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061

Phone: 800-466-7126
www.rustoleum.com

Form: ARJ-1929
Rev.: 110719