



## PENETRATING OIL

LIQUID WRENCH® Penetrating Oil with CERFLON® is a fast-acting, anti-seize formula that penetrates corrosion, and loosens rusted bolts and parts.

**BENEFITS:** Frees stuck nuts, bolts and locks • Dissolves rust and cuts through grease • 50-state compliant • Low odor, 0% VOC and safe on painted surfaces

**DIRECTIONS:** Mix well. Apply to rusted parts. Allow to soak. Tap or vibrate parts to enhance penetration. Get Material Safety Data Sheet via 704-821-7643 or [liquidwrench.com](http://liquidwrench.com).

**STORAGE, HANDLING & DISPOSAL:** Do not expose to heat, sparks or open flames. Store in a cool, dry area below 120°F/49°C. Do not use pressure to empty this container. Dispose of product, container and residue according to all local, state and federal laws and regulations. When empty, container may contain vapor or product residue. Do not reuse this container for any purpose. When disposing of unused contents, send to licensed reclaimers or authorized incinerators. Do not dump into sewers, on the ground, or into any body of water. All cautions apply to empty containers after product use.

**DANGER:** Use only in a well-ventilated area away from heat, sparks and flames. Do not place container in contact with hot surfaces because of risk of fire. Use added caution in confined areas such as basements and automobile compartments. **BREATHING & INGESTION HAZARDS:** INHALING CONCENTRATED VAPORS, INTENTIONALLY OR OTHERWISE MAY CAUSE DEATH WITHOUT WARNING. Harmful or fatal if swallowed. **CONTACT HAZARD:** Eye and skin irritant. Prolonged skin contact may cause dermatitis.

**FIRST AID:** **EYE CONTACT:** Flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. **SKIN CONTACT:** Wash with soap and water. If irritation develops, get prompt medical attention. **INHALATION:** Move to fresh air. If breathing becomes difficult, get prompt medical attention. **INGESTION:** DO NOT INDUCE VOMITING. Call Poison Control Center, Physician or Hospital Emergency Room immediately.

### KEEP AWAY FROM CHILDREN AND ANIMALS

L134	Plastic Jug, 1 gal. 078698120188
L140	Pail, 5 gal. 078698120102
L149	Metal Drum, 54 gal. 078698120195

**NOTICE:** While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.