



Mega Textured nitrile gloves that offer a comfortable, confident grip when handling wet, oily, or fatty foods and objects

- Feature a Mega Texture surface for secure grip
- Have a generous fit for comfortable use with a cut-protective or thermal under gloves
- The robust 0.20 mm/8 mil thickness resists tearing, for product protection
- Compliant with US Food Contact and EU Food Migration Regulations



Industries

- Food Processing
- Janitorial / Sanitation

Recommended For

- Packaging and labeling
- Food processing and handling
- Cold storage
- Deboning, carving
- Handling of frozen foods
- Janitorial, clean up and maintenance
- Processing meat, vegetables and dairy sanitation
- Secondary food processing



TECHNICAL DATA SHEET

PRODUCT INFORMATION

| | 93-287 |
|--|---|
| Material | Nitrile |
| Color | Green |
| Glove Design | Powder-Free, Chlorinated, Raised Diamond Grip Pattern |
| Cuff | Beaded |
| Regulatory/Standards Compliance | ASTM D6319, EC 2023/2006, EC 1935/2004, EN ISO 374-1:2016, EN 420:2003 + A1:2009, EN 420:2003 + A1:2009, EN ISO 374-5:2016, FDA21 CFR 177-2600, ISO 9001, ISO 13485 |
| Packaging | 50 gloves per dispenser; 10 dispensers per case; 500 gloves per case; 2XL and 3XL: 44 gloves per dispenser; 440 gloves per case |
| Storage | Keep out of direct sunlight store in a cool and dry place Keep away from sources of ozone or ignition. |
| Country of Origin | Malaysia |
| User Needs Segment | High Risk |
| Available sizes | S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10), XXL (10.5 - 11), XXXL (11.5 - 12) |
| Anti-static | No |
| Vulcanization Chemical Accelerators | <ul style="list-style-type: none"> Zinc Dibutyldithiocarbamate (ZDBC) Zinc Diethyldithiocarbamate (ZDEC) <p><i>Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.</i></p> |

PHYSICAL PROPERTIES

| | Typical Values | | Testing Method |
|---|----------------|-------------|---------------------|
| Length (mm/inches) | 300 / 11.8 | | ASTM D3767,EN 420 |
| Freedom from Holes (Inspection level I) | 1.5 AQL | | ASTM D5151,EN 374-2 |
| Palm Thickness (mm/mils) | 0.20 / 7.9 | | ASTM D3767,EN 420 |
| Finger Thickness (mm/mils) | 0.22 / 8.7 | | ASTM D3767,EN 420 |
| | BEFORE AGING | AFTER AGING | |
| Ultimate Tensile Strength (MPa) | 28 | 25 | ASTM D412 & D573 |
| Elongation at Break (%) | 450 | 420 | ASTM D412 |
| Force at break (N) | 10 | 6 | EN 455-2 |

ORDERING INFORMATION

| Size | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) | XXL (10.5 - 11) | XXXL (11.5 - 12) |
|--------------|-------------|-------------|-------------|---------------|-----------------|------------------|
| Product Code | 93287070 | 93287080 | 93287090 | 93287100 | 93287110 | 93287120 |

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center
(Malaysia) Sdn Bhd
T: +603 8310 6688
F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.
T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia

Ansell PYC
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2020 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.