

PP 803



PREMIUM PLUS GRADE SOLVENT-BASED ACRYLIC LABEL PROTECTION & PACKAGING TAPE

TYPICAL APPLICATIONS

- For overlamination, label protection and carton closure applications that demand 100 percent clarity

PRODUCT FEATURES

- Clear to the core with 100 percent clarity – no streaks, dust or other contaminants
- Excellent holding power
- Performs in a range of temperatures

CONSTRUCTION

Overall Grade/Function: Premium plus

Backing: 30 micron biaxially oriented polypropylene cast film

Adhesive: Crystal clear, solvent-based acrylic

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

50 m

Contact your Shurtape sales representative for other available sizes

APPLICABLE STANDARDS

CID A-A-1684C

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	25 lbs/in width	43.8 N/10 mm
Adhesion to Stainless Steel	25 oz/in width	2.74 N/10 mm
Thickness	2.2 mils	0.06 mm
Elongation	150%	150%
Application Temperature Range	20 F to 110 F	-7 C to 43 C
Service Temperature Range	-20 F to 180 F	-29 C to 82 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

