

## Build Your Own Berm Straight Section #BYOB-2S - 15' x 5.5" x 2", 1/package



Build your own barrier around equipment or storage, indoors or out.

- Semi-permanent, highly visible berm is customizable to your desired size and shape
- Vinyl covered foam barrier resists oils, coolants and most chemicals
- Recovers its shape under foot traffic or light, wheeled equipment
- Easy to cut with utility knife
- Secure to smooth surfaces with Sili-Thane (BYOB-SEAL) sealant or join seams with Industrial Strength Vinyl Cement (BYOB-CEMENT)
- Inexpensive and easy-to-install containment alternative to cement curbs or angle iron
- Simple removal with flat-bladed shovel
- Ideal for leak-prone areas like battery charging stations or machinery

### BYOB-2S Specifications

<b>Dimensions:</b>	5.5" W x 15' L x 2" H
<b>Shipping Dimensions:</b>	30.33" W x 30.33" L x 6.75" H
<b>Sold as:</b>	1 per package
<b>Color:</b>	Yellow
<b>Composition:</b>	18oz All-Vinyl Covering with Open-Cell Foam Interior
<b>Weight:</b>	6 lbs.
<b># per Pallet:</b>	24
<b>Incinerable:</b>	No
<b>Ship Class:</b>	300

### Metric Equivalent Specifications

<b>Dimensions:</b>	14cm W x 4.6m L x 5.1cm H
<b>Shipping Dimensions:</b>	77cm W x 77cm L x 17.1cm H
<b>Dimensions:</b>	
<b>Weight:</b>	2.7 kg

## BYOB-2S Technical Information

### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

### Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

40 CFR 122.26 - Facilities must have a detailed plan in place to prevent illegal discharge of pollutants into waterways.

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

### Technical Documents:

(Available at [spilltech.com](http://spilltech.com))

Product Data Sheet (PDS)



Online:  
[spilltech.com](http://spilltech.com)

Phone:  
**1-800-228-3877 (N.Am.)**  
**1-770-475-3877 (Other)**

Fax:  
**1-800-872-3764 (N.Am.)**  
**1-770-410-1812 (Other)**

Email:  
[sales@spilltech.com](mailto:sales@spilltech.com)