

# White Lightning® Silicone Ultra Gutter & Flashing Sealant

<b>Physical Properties:</b>		<b>Silicone Ultra Gutter &amp; Flashing Sealant</b>	
<b>Type:</b>	100% Silicone	<b>Application Temperature:</b>	40°F to 140°F
<b>Color:</b>	White, Clear, Gray	<b>Service Temperature:</b>	-80°F to 450°F
<b>Shelf Life:</b>	12 Months	<b>Odor:</b>	Low
<b>Full Cure Time:</b>	24 Hours	<b>Vehicle:</b>	Solvent Based
<b>Tack Free Time:</b>	30 Minutes	<b>Weight/Gallon:</b>	8.5 lbs/gal
<b>Performance Data:</b>			
<b>Joint Movement Capability:</b>	Permanently Flexible	<b>Rust Resistance:</b>	Excellent
<b>Joint Size:</b>	1/2" x 1/2"	<b>Shrinkage:</b>	Low
<b>Clean-Up:</b>	Mineral Spirits	<b>Linear Coverage:</b>	
<b>Flexibility:</b>	Excellent	<b>10 oz Cartridge</b>	
<b>Painting:</b>	Do Not Paint	<b>1/8" Bead Application</b>	96.7 ft
<b>Mildew Resistance:</b>	Excellent	<b>1/4" Bead Application</b>	24.2 ft
<b>Water Resistance:</b>	Excellent		

## White Lightning® Asphalt Roof Sealant

<b>Physical Properties:</b>		<b>Asphalt Roof Sealant</b>
<b>Type:</b>	Roof Cement	
<b>Color:</b>	Black	
<b>Shelf Life:</b>	12 Months	
<b>Flash Point:</b>	107°F	
<b>Full Cure Time:</b>	24-48 Hours	
<b>Application Temperature:</b>	Above 32°F	
<b>Service Temperature:</b>	-40°F to 180°F	
<b>Odor:</b>	Solvent Like	
<b>Vehicle:</b>	Solvent Based	
<b>Performance Data:</b>		
<b>Joint Movement Capability:</b>	Moderate	
<b>Joint Size:</b>	1/8" x 1/8" to 1/2" x 1/4"	
<b>Freeze-Thaw Stability:</b>	Stable Through 5 Cycles	
<b>Clean Up:</b>	Mineral Spirits	
<b>Flexibility:</b>	Excellent	
<b>Painting:</b>	Do Not Paint	
<b>Mildew Resistance:</b>	Good	
<b>Water Resistance:</b>	Excellent	
<b>Shrinkage:</b>	Low	
<b>Linear Coverage:</b>		
<b>10 oz Cartridge</b>		
<b>1/8" Bead Application</b>	96.7 ft	
<b>1/4" Bead Application</b>	24.2 ft	

## White Lightning® Butyl Rubber Caulk

<b>Physical Properties:</b>		<b>Butyl Rubber Caulk</b>
<b>Type:</b>	Premium Sealant	
<b>Color:</b>	White	
<b>Shelf Life:</b>	12 Months	
<b>Flash Point:</b>	175°F	
<b>Full Cure Time:</b>	24 to 48 hours	
<b>Application Temperature:</b>	Above 40°F	
<b>Service Temperature:</b>	-40°F to 180°F	
<b>Odor:</b>	Solvent Like	
<b>Shrinkage:</b>	Low	
<b>Vehicle:</b>	Solvent Based	
<b>Weight Solids:</b>	92%	
<b>Weight/Gallon:</b>	11.32 lbs/gal	
<b>Performance Data:</b>		
<b>Joint Movement Capability:</b>	Moderate	
<b>Joint Size:</b>	1/2" x 1/4" to 1/8" x 1/8"	
<b>Freeze-Thaw Stability:</b>	Stable Through 5 Cycles	
<b>Clean Up:</b>	Mineral spirits	
<b>Flexibility:</b>	Excellent	
<b>Painting:</b>	Do Not Paint	
<b>Water Resistance:</b>	Excellent	
<b>Mildew Resistance:</b>	Good	
<b>Linear Coverage:</b>		
<b>10 oz Cartridge</b>		
<b>1/8" Bead Application</b>	96.7 ft	
<b>1/4" Bead Application</b>	24.2 ft	



For more information please call or write:

White Lightning® Products • 101 Prospect Ave. NW • Cleveland, OH 44115  
 1-800-241-5295 Option 1 Customer Service • 1-800-241-5295 Option 2 Technical Service  
[www.wlcaulk.com](http://www.wlcaulk.com)

Part # WP00037