

# SAFETY DATA SHEET

{ error: graphic file not  
found: E:\Program  
Files\Apache Software  
Foundation\Tomcat  
7.0\webapps\ehswww\WEB-  
INF\bin\graphics\ZepIncLogo  
.BMP }

## ZEP STAINLESS STEEL POL Z

Version 4.0

Revision Date 02/20/2018

Print Date 03/26/2018

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP STAINLESS STEEL POL Z

Material number : ZUSSTL14

#### Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE  
Emerson, GA 30137

Telephone : 404-352-1680

#### Emergency telephone numbers

**For SDS Information** : Compliance Services 1-877-428-9937

**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded

**For a Transportation  
Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616

#### Recommended use of the chemical and restrictions on use

Recommended use : Cleaner

Note: This product is labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations. The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance	Aerosol containing a compressed gas
Colour	amber
Odour	characteristic

#### GHS Classification

Flammable aerosols : Category 1  
Gases under pressure : Compressed gas  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Skin sensitisation : Category 1

#### GHS label elements

# SAFETY DATA SHEET

{ error: graphic file not  
found: E:\Program  
Files\Apache Software  
Foundation\Tomcat  
7.0\webapps\ehswww\WEB-  
INF\bin\graphics\ZepIncLogo  
.BMP }

## ZEP STAINLESS STEEL POL Z

Version 4.0

Revision Date 02/20/2018

Print Date 03/26/2018

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.

Precautionary statements

: **Prevention:**  
P210 Keep away from heat/sparks/open flames/hot surfaces.  
No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.  
**Storage:**  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.  
**Disposal:**  
P501 Dispose of contents/container in accordance with local regulation.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

### Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 50 - < 70
Distillates (petroleum), hydrotreated light	64742-47-8	>= 10 - < 20
Solvent naphtha (petroleum), light aliph.	64742-89-8	>= 5 - < 10

# SAFETY DATA SHEET

{ error: graphic file not  
found: E:\Program  
Files\Apache Software  
Foundation\Tomcat  
7.0\webapps\ehswww\WEB-  
INF\bin\graphics\ZepIncLogo  
.BMP }

## ZEP STAINLESS STEEL POL Z

Version 4.0

Revision Date 02/20/2018

Print Date 03/26/2018

Citrus, ext.	94266-47-4	>= 1 - < 5
carbon dioxide	124-38-9	>= 1 - < 5
Solvent naphtha (petroleum), heavy aliph.	64742-96-7	>= 1 - < 5
propan-2-ol	67-63-0	>= 1 - < 5
citral	5392-40-5	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.  
Wash off immediately with plenty of water for at least 15 minutes.  
Remove contaminated clothing and shoes.  
Wash contaminated clothing before reuse.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.  
Rinse immediately with plenty of water for at least 15 minutes.
- If swallowed : Keep respiratory tract clear.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.  
Symptoms may include irritation, redness, pain, and rash.  
Effects are dependent on exposure (dose, concentration, contact time).  
Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam

# SAFETY DATA SHEET

{ error: graphic file not  
found: E:\Program  
Files\Apache Software  
Foundation\Tomcat  
7.0\webapps\ehswww\WEB-  
INF\bin\graphics\ZepIncLogo  
.BMP }

## ZEP STAINLESS STEEL POL Z

Version 4.0

Revision Date 02/20/2018

Print Date 03/26/2018

	Carbon dioxide (CO2) Dry chemical Water spray jet
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

## SECTION 7. HANDLING AND STORAGE

# SAFETY DATA SHEET

{ error: graphic file not  
found: E:\Program  
Files\Apache Software  
Foundation\Tomcat  
7.0\webapps\ehswww\WEB-  
INF\bin\graphics\ZepIncLogo  
.BMP }

## ZEP STAINLESS STEEL POL Z

Version 4.0

Revision Date 02/20/2018

Print Date 03/26/2018

- Advice on safe handling : Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Always replace cap after use.  
Do not breathe vapours or spray mist.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
No smoking.  
Observe label precautions.  
Keep in a dry, cool and well-ventilated place.  
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Strong oxidizing agents

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL

# SAFETY DATA SHEET

{ error: graphic file not  
found: E:\Program  
Files\Apache Software  
Foundation\Tomcat  
7.0\webapps\ehswww\WEB-  
INF\bin\graphics\ZepIncLogo  
.BMP }

## ZEP STAINLESS STEEL POL Z

Version 4.0

Revision Date 02/20/2018

Print Date 03/26/2018

carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m3	NIOSH REL
		ST	30,000 ppm 54,000 mg/m3	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m3	OSHA Z-1
		TWA	10,000 ppm 18,000 mg/m3	OSHA P0
		STEL	30,000 ppm 54,000 mg/m3	OSHA P0
		PEL	5,000 ppm 9,000 mg/m3	CAL PEL
		STEL	30,000 ppm 54,000 mg/m3	CAL PEL
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
		PEL	400 ppm 980 mg/m3	CAL PEL
		STEL	500 ppm 1,225 mg/m3	CAL PEL
citral	5392-40-5	TWA (Inhalable fraction and vapor)	5 ppm	ACGIH

### Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI

**Engineering measures** : effective ventilation in all processing areas

### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

# SAFETY DATA SHEET

{ error: graphic file not  
found: E:\Program  
Files\Apache Software  
Foundation\Tomcat  
7.0\webapps\ehswww\WEB-  
INF\bin\graphics\ZepIncLogo  
.BMP }

## ZEP STAINLESS STEEL POL Z

Version 4.0

Revision Date 02/20/2018

Print Date 03/26/2018

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

### Hand protection

#### Material

: Protective gloves

#### Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

### Eye protection

: Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.

Tightly fitting safety goggles

### Skin and body protection

: Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

### Hygiene measures

: When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### Appearance

: Aerosol containing a compressed gas

### Colour

: amber

### Odour

: characteristic

### Odour Threshold

: No data available

### pH

: Not applicable

### Melting point/freezing point

: No data available

### Boiling point

: 82.22 °C

### Flash point

:  
No data available

### Evaporation rate

: No data available

### Flammability (solid, gas)

: Extremely flammable aerosol.

### Upper explosion limit

: No data available

### Lower explosion limit

: No data available

### Vapour pressure

: No data available

### Relative vapour density

: No data available

### Density

: 0.846 g/cm<sup>3</sup>

### Solubility(ies)

# SAFETY DATA SHEET

{ error: graphic file not  
found: E:\Program  
Files\Apache Software  
Foundation\Tomcat  
7.0\webapps\ehswww\WEB-  
INF\bin\graphics\ZepIncLogo  
.BMP }

## ZEP STAINLESS STEEL POL Z

Version 4.0

Revision Date 02/20/2018

Print Date 03/26/2018

Water solubility	: insoluble
Solubility in other solvents	: not determined
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Heat of combustion	: 44.04 kJ/g

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon oxides

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Effects are dependent on exposure (dose, concentration, contact time).

#### Carcinogenicity:



# SAFETY DATA SHEET

{ error: graphic file not  
found: E:\Program  
Files\Apache Software  
Foundation\Tomcat  
7.0\webapps\ehswww\WEB-  
INF\bin\graphics\ZepIncLogo  
.BMP }

## ZEP STAINLESS STEEL POL Z

Version 4.0

Revision Date 02/20/2018

Print Date 03/26/2018

<b>IARC</b>	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
<b>ACGIH</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
<b>OSHA</b>	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
<b>NTP</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Acute toxicity

#### Product:

Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method

#### Components:

##### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Acute oral toxicity	: LD50 Rat: > 5,000 mg/kg
Acute inhalation toxicity	: LC50 Rat: > 5 mg/l Exposure time: 4 h
Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg

##### **Distillates (petroleum), hydrotreated light:**

Acute oral toxicity	: LD50 Rat: > 5,000 mg/kg
Acute inhalation toxicity	: LC50 Rat: > 4.6 mg/l Exposure time: 6 h
Acute dermal toxicity	: LD50 Rat: > 2,000 mg/kg

##### **propan-2-ol:**

Acute oral toxicity	: LD50 Oral Rat: 4,396 mg/kg Method: Calculation method
---------------------	--

### Skin corrosion/irritation

#### Product:

# SAFETY DATA SHEET

{ error: graphic file not  
found: E:\Program  
Files\Apache Software  
Foundation\Tomcat  
7.0\webapps\ehswww\WEB-  
INF\bin\graphics\ZepIncLogo  
.BMP }

## ZEP STAINLESS STEEL POL Z

Version 4.0

Revision Date 02/20/2018

Print Date 03/26/2018

Remarks: Irritating to skin.

### Serious eye damage/eye irritation

#### Product:

Remarks: Irritating to eyes.

### Respiratory or skin sensitisation

#### Product:

Remarks: Causes sensitisation.

### Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

### Reproductive toxicity

No data available

### STOT - single exposure

No data available

### STOT - repeated exposure

No data available

### Aspiration toxicity

No data available

### Further information

#### Product:

Remarks: No data available

#### Components:

Distillates (petroleum), hydrotreated light:

Remarks: No data available

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

# SAFETY DATA SHEET

{ error: graphic file not  
found: E:\Program  
Files\Apache Software  
Foundation\Tomcat  
7.0\webapps\ehswww\WEB-  
INF\bin\graphics\ZepIncLogo  
.BMP }

## ZEP STAINLESS STEEL POL Z

Version 4.0

Revision Date 02/20/2018

Print Date 03/26/2018

### Citrus, ext. :

Toxicity to fish : LC50 (Fish): 0.1 - 1.0 mg/l  
Remarks: Information taken from reference works and the literature.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.1 - 1.0 mg/l  
Remarks: Information taken from reference works and the literature.

### Persistence and degradability

#### Components:

##### Citrus, ext. :

Biodegradability : Remarks: Readily biodegradable  
Information taken from reference works and the literature.

### Bioaccumulative potential

#### Product:

Partition coefficient: n-octanol/water : Remarks: No data available

#### Components:

##### Citrus, ext. :

Bioaccumulation : Bioconcentration factor (BCF): < 2,000  
Remarks: Information taken from reference works and the literature.

##### citral :

Partition coefficient: n-octanol/water : Pow: 2.76

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

#### Components:

# SAFETY DATA SHEET

{ error: graphic file not  
found: E:\Program  
Files\Apache Software  
Foundation\Tomcat  
7.0\webapps\ehswww\WEB-  
INF\bin\graphics\ZepIncLogo  
.BMP }

## ZEP STAINLESS STEEL POL Z

Version 4.0

Revision Date 02/20/2018

Print Date 03/26/2018

### Distillates (petroleum), hydrotreated light :

Additional ecological information : No data available

### Citrus, ext. :

Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT)., Remarks: Information taken from reference works and the literature.

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

## SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

# SAFETY DATA SHEET

{ error: graphic file not  
found: E:\Program  
Files\Apache Software  
Foundation\Tomcat  
7.0\webapps\ehswww\WEB-  
INF\bin\graphics\ZepIncLogo  
.BMP }

## ZEP STAINLESS STEEL POL Z

Version 4.0

Revision Date 02/20/2018

Print Date 03/26/2018

### SECTION 15. REGULATORY INFORMATION

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### EPCRA - Emergency Planning and Community Right-to-Know Act

##### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Gases under pressure  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Respiratory or skin sensitisation

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL  
**TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

#### Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

# SAFETY DATA SHEET

{ error: graphic file not  
found: E:\Program  
Files\Apache Software  
Foundation\Tomcat  
7.0\webapps\ehswww\WEB-  
INF\bin\graphics\ZepIncLogo  
.BMP }

## ZEP STAINLESS STEEL POL Z

Version 4.0


Revision Date 02/20/2018

Print Date 03/26/2018

### SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA:



##### HMIS III:

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

### OSHA - GHS Label Information:

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated.  
Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statements

: **Prevention:** Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/eye protection/face protection.  
**Response:** IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.  
**Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.  
**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	4.0
Revision Date:	02/20/2018
Print Date:	03/26/2018

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it

# SAFETY DATA SHEET

{ error: graphic file not  
found: E:\Program  
Files\Apache Software  
Foundation\Tomcat  
7.0\webapps\ehswww\WEB-  
INF\bin\graphics\ZepIncLogo  
.BMP }

## ZEP STAINLESS STEEL POL Z

Version 4.0

Revision Date 02/20/2018

Print Date 03/26/2018

is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.